

IE-CSQS9VE0260AQEAQE-K1

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Assembled IE cables

General ordering data

Version	System cable, V14 hybrid (shielded), V14 hybrid (shielded), PVC, 26 m, , Hybrid
Order No.	1465850260
Type	IE-CSQS9VE0260AQEAQE-K1
GTIN (EAN)	4050118272437
Qty.	1 pc(s).

Creation date June 12, 2025 12:36:21 PM CEST

Catalogue status 07.06.2025 / We reserve the right to make technical changes.

IE-CSQS9VE0260AQEAQE-K1

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	26 m	Length (inches)	1,023.622 inch
Net weight	3,240 g		

Temperatures

Operating temperature	-40 °C...80 °C
-----------------------	----------------

Electrical properties

Insulation strength	> 500 MΩ	Operating voltage	300 V
---------------------	----------	-------------------	-------

General standards

Connector standard	IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14
--------------------	--

Standards

Connector standard	IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14
--------------------	--

Cable structure

Cable layout	Hybrid cable, for permanent installation	Cross-section	2 x 0.34 mm ² + 7 x 0.5 mm ²
Insulation	PP	Insulation cross-section	1.25 mm
Insulation diameter 2	2.15 mm	Material sheath	PVC
Overlap of shielding braid	85 %	Sheath diameter, max.	9.5 mm
Sheath diameter, min.	9.1 mm	Sheathing colour	black

Electrical properties of cable

Insulation strength	> 500 MΩ	Operating voltage	300 V
---------------------	----------	-------------------	-------

Mechanical and material properties of cable

Min. bending radius, once only	5 x cable diameter	Min. bending radius, repetitive	10 x cable diameter
--------------------------------	--------------------	---------------------------------	---------------------

Plug, left

Plug left	Q10 Hybrid, IP67, female contact, straight, PushPull V14, plug, Zinc diecast, shielded
-----------	--

Plug, right

Plug right	Q10 Hybrid, IP67, female contact, straight, PushPull V14, plug, Zinc diecast, shielded
------------	--

IE-CSQS9VE0260AQEAQE-K1

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC001579	ETIM 7.0	EC001579
ETIM 8.0	EC001579	ETIM 9.0	EC001579
ETIM 10.0	EC001579	ECLASS 9.0	27-06-24-90
ECLASS 9.1	27-06-24-00	ECLASS 10.0	27-06-05-01
ECLASS 11.0	27-06-05-01	ECLASS 12.0	27-06-05-01
ECLASS 13.0	27-06-05-01	ECLASS 14.0	27-06-05-01
ECLASS 15.0	27-06-05-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant
REACH SVHC	Lead 7439-92-1

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN PI PROFINET CABLING EN

Data sheet


IE-CSQS9VE0260AQEAQE-K1

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Drawings

Wiring



STECKANLEITUNG
TYPE 9000

Pin	Color	Designation
1	Blue	PAIR 1 (B)
2	White	PAIR 1 (B)
3	Red	PAIR 2 (B)
4	Black	PAIR 2 (B)
5	Green	PAIR 3 (B)
6	Yellow	PAIR 3 (B)
7	Grey	PAIR 4 (B)
8	Brown	PAIR 4 (B)
9	Orange	PAIR 5 (B)
10	Purple	PAIR 5 (B)
11	Light Blue	PAIR 6 (B)
12	Light Green	PAIR 6 (B)