




# Coupled Inductors MSD1514



**Core material** Ferrite

**Core and winding loss** [Go to online calculator](#)

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant matte tin over nickel over phosphorous. Other terminations available at additional cost.

**Weight:** 9.0 – 11.8 g

**Ambient temperature** –40°C to +85°C with (40°C rise) Irms current.

**Maximum part temperature** +125°C (ambient + temp rise).

**Storage temperature** Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

**Winding-to-winding isolation** 500 Vrms, one minute





**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Packaging** 175/13" reel; Plastic tape: 32 mm wide, 0.5 mm thick, 24 mm pocket spacing, 14.3 mm pocket depth

**PCB washing** Tested with pure water or alcohol only. For other solvents, see [Doc787\\_PCB\\_Washing.pdf](#).

- Excellent coupling coefficient ( $k \geq 0.97$ )
- Ideal for use in a variety of circuits including flyback, multi-output buck, SEPIC, Zeta, and Cuk.
- High inductance, high efficiency and excellent current handling.
- In SEPIC topologies, the required inductance is half the value needed for two separate inductors, allowing selection of a part with lower DCR and higher current handling.





# MSD1514 Coupled Inductors

Part number <sup>1</sup>	Inductance <sup>2</sup> ( $\mu$ H)	DCR (Ohms) <sup>3</sup>		SRF typ <sup>4</sup> (MHz)	Coupling coefficient typ	Leakage inductance typ ( $\mu$ H)	Isat (A) <sup>5</sup>			Irms (A)	
		typ	max				10% drop	20% drop	30% drop	both windings <sup>6</sup>	one winding <sup>7</sup>
MSD1514-252ME	2.5 ±20%	0.010	0.012	34.0	0.97	0.20	25.0	28.0	30.5	6.0	7.8
MSD1514-472ME	4.7 ±20%	0.012	0.014	25.0	0.98	0.20	19.5	21.8	23.7	5.4	7.6
MSD1514-103ME	10 ±20%	0.015	0.018	16.5	0.99	0.40	13.4	15.0	16.2	4.8	6.8
MSD1514-123ME	12 ±20%	0.018	0.022	14.5	0.99	0.40	12.2	13.7	14.8	4.7	6.6
MSD1514-153ME	15 ±20%	0.024	0.028	11.0	>0.99	0.42	10.9	12.2	13.3	4.1	5.8
MSD1514-223ME	22 ±20%	0.031	0.036	10.0	>0.99	0.45	9.00	10.1	11.0	3.6	5.1
MSD1514-273ME	27 ±20%	0.034	0.039	8.50	>0.99	0.45	8.14	9.13	9.90	3.5	4.7
MSD1514-333ME	33 ±20%	0.045	0.052	7.20	>0.99	0.45	7.40	8.20	9.00	3.0	3.9
MSD1514-473ME	47 ±20%	0.065	0.075	5.60	>0.99	0.55	6.20	6.90	7.50	2.6	3.45
MSD1514-683ME	68 ±20%	0.078	0.090	5.20	>0.99	0.55	5.10	5.70	6.20	2.2	3.20
MSD1514-104KE	100 ±10%	0.115	0.126	3.80	>0.99	0.55	4.20	4.75	5.15	2.0	2.50
MSD1514-224KE	220 ±10%	0.261	0.287	2.30	>0.99	0.70	2.85	3.20	3.50	1.3	1.70
MSD1514-334KE	330 ±10%	0.334	0.367	2.10	>0.99	0.80	2.33	2.61	2.83	1.2	1.55
MSD1514-474KE	470 ±10%	0.500	0.550	1.65	>0.99	1.2	1.95	2.20	2.40	0.92	1.30
MSD1514-105KE	1000 ±10%	1.12	1.25	1.10	>0.99	2.0	1.34	1.50	1.63	0.66	0.77

1. When ordering, please specify **termination** and **packaging** codes:

**MSD1514-105KE**

**Termination:** **E** = RoHS compliant matte tin over nickel over phosphorous bronze. Special order: **Q** = RoHS tin-silver-copper (95.5/4.0/5) or **P** = non-RoHS tin-lead (63/37).

**Packaging:** **D** = 13" machine-ready reel. EIA-481 embossed plastic tape (175 parts per full reel). Quantities less than full reel available: in tape (not machine ready) or with leader and trailer (\$25 charge).

**B** = Less than full reel. In an effort to simplify our part numbering system, Coilcraft is eliminating the need for multiple packaging codes. When ordering, simply change the last letter of your part number from B to D.

2. Inductance shown for each winding, measured at 100 kHz, 0.1 Vrms, 0 Adc on an Agilent/HP 4284A LCR meter or equivalent. When leads are connected in parallel, inductance is the same value. When leads are connected in series, inductance is four times the value.

3. DCR is for each winding. When leads are connected in parallel, DCR is half the value. When leads are connected in series, DCR is twice the value.

4. SRF measured using an Agilent/HP 4191A or equivalent. When leads are connected in parallel, SRF is the same value.

5. DC current at which the inductance drops the specified amount from its value without current. It is the sum of the current flowing in both windings.

6. Equal current when applied to each winding simultaneously that causes a 40°C temperature rise from 25°C ambient.

[Click for temperature derating information.](#)

7. Maximum current when applied to one winding that causes a 40°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

[Click for temperature derating information.](#)

8. Electrical specifications at 25°C.

Refer to Doc 639 "Selecting Coupled Inductors for SEPIC Applications."

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

## Coupled Inductor Core and Winding Loss Calculator

This web-based utility allows you to enter frequency, peak-to-peak (ripple) current, and Irms current to predict temperature rise and overall losses, including core loss. [Go to online calculator.](#)



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** +65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 1308-2 Revised 03/09/23

© Coilcraft Inc. 2023

This product may not be used in medical or high

risk applications without prior Coilcraft approval.


Specification subject to change without notice.

Please check web site for latest information.








# MSD1514 Coupled Inductors

## Typical L vs Current



## Typical L vs Frequency



Recommended Land Pattern

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$

\* For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.012 inch (0,3 mm).

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Coilcraft:

[MSD1514-472MEB](#) [MSD1514-333MED](#) [MSD1514-473MEB](#) [MSD1514-105KED](#) [MSD1514-223MED](#) [MSD1514-334KEB](#) [MSD1514-224KED](#) [MSD1514-103MED](#) [MSD1514-123MED](#) [MSD1514-474KEB](#) [MSD1514-474KED](#) [MSD1514-252MEB](#) [MSD1514-683MEB](#) [MSD1514-334KED](#) [MSD1514-104KEB](#) [MSD1514-223MED](#) [MSD1514-333MEB](#) [MSD1514-123MEB](#) [MSD1514-153MED](#) [MSD1514-683MED](#) [MSD1514-103MEB](#) [MSD1514-273MEB](#) [MSD1514-473MED](#) [MSD1514-472MED](#) [MSD1514-105KEB](#) [MSD1514-153MEB](#) [MSD1514-252MED](#) [MSD1514-224KEB](#) [MSD1514-273MED](#) [MSD1514-104KED](#) [MSD1514-184KED](#) [MSD1514-124KEB](#) [MSD1514-274KEB](#) [MSD1514-124KED](#) [MSD1514-393MED](#) [MSD1514-392MEB](#) [MSD1514-394MEB](#) [MSD1514-684KEB](#) [MSD1514-184KEB](#) [MSD1514-563MEB](#) [MSD1514-564KEB](#) [MSD1514-154KEB](#) [MSD1514-824KEB](#) [MSD1514-824KED](#) [MSD1514-822MED](#) [MSD1514-393MEB](#) [MSD1514-154KED](#) [MSD1514-652MED](#) [MSD1514-183MEB](#) [MSD1514-392MED](#) [MSD1514-652MEB](#) [MSD1514-564KED](#) [MSD1514-684KED](#) [MSD1514-822MEB](#) [MSD1514-823MED](#) [MSD1514-394MED](#) [MSD1514-183MED](#) [MSD1514-563MED](#) [MSD1514-823MEB](#) [MSD1514-274KED](#)